

SILICONE SUNDRY PRODUCTS

SILICONE WAX EMULSION SIL3100

This product is a specialist blend of wax compounds, which can be added to the silicone/water blend on a heatset press to impart extra rub resistance.

Although Stehlin Hostag silicones contain optimum levels of wax on difficult papers extra wax can be added at the point of application. If the higher levels of wax were added during production, separation could occur on storage.

Silicone Wax Emulsion can be dosed easily on site to achieve the following affects.

- Select to improve the surface slip and ensure optimum rub and scuff resistance
- Particularly helpful to overcome marking on matt coated papers
- Gives protection to the printed web through demanding finishing operations

Silicone Wax Emulsion should be dosed at 1% to 2%. Please note it is important not to use this product over remoist adhesives. This product is available in 10kg containers.

SILSTAT ANTI STATIC SOLUTION SIL3000

For use with Silicone Emulsions on web offset heatset presses, recommended dosage is 1-4%.

This product has been developed as an alternative to using Comfort fabric conditioner. Unlike Comfort, the formulation ensures complete compatibility with our Silicone Emulsions and is not subject to variations that may cause issues in the future which the printer would have no knowledge of.

Packaging

25kg containers

IT IS IMPORTANT TO NOTE THAT THESE PRODUCTS HAVE A SHELF LIFE OF 12 MONTHS FROM DATE OF DELIVERY.