



*Stehlin Hostag Ink U.K. Ltd
Unit D4, Linkmel Close, Longwall Avenue,
Queens Drive Industrial Estate,
Nottingham. NG2 1NA
Tel: 0115 986 0477
Fax: 0115 986 2681*

Date of Issue: 10/10/02

TDS 5/010

UV WEB GLOSS LACQUER 3022

Stehlin Hostag Ink UK Ltd are in partnership with Schmid Rhyner AG who have many years experience in print finishing and are the leading producer in Europe of overprint primers and UV varnishes. Schmid Rhyner through Stehlin Hostag will be able to provide you with the most technologically advanced Web UV lacquer or varnish system in today's markets, giving you greater flexibility and productivity. All Schmid Rhyner products meet the latest stringent European legislation with regards to raw material selection.

With a wide and exciting range of products available we recommend you contact our laboratories at time of ordering to review all the technical requirements for you preferred application.

Schmid Rhyner Wessco Web UV Gloss Lacquers exhibit the following properties:

- Excellent gloss
- Good slip
- Very high reactivity
- Scuff resistance
- Scratch resistance
- Chemical resistance
- Die cutability
- Embossability
- Low odour
- High flexibility

Recommendations

- Use only coated paper and board with low absorbency and condition for at least 12 hours in the production room.
- After printing let stack rest for 12 hours
- Use solvent and alkali resistant inks
- Do not use ink with a high wax content
- Consult ink supplier before using metallic inks



Stehlin Hostag Ink U.K. Ltd
Unit D4, Linkmel Close, Longwall Avenue,
Queens Drive Industrial Estate,
Nottingham. NG2 1NA
Tel: 0115 986 0477
Fax: 0115 986 2681

Date of Issue: 10/10/02
Cont/d... (sheet two)

TDS 5/010

- UV-lamps – minimum capacity 80w/cm
- Machine speeds dependant on substrate amount of power and condition of the UV lamps
- Application – Rollercoat System
- Anilox System
- Cleaning – ensure machine is clean after use

Labelling Irritant (Xi)

Storage In original closed container for 6 months at 10-25°C
Important Note – Stir well before use

Packaging 25kg container
 125kg container
 1000kg container

Printing Auxiliaries

Delta UV Premium Wash D1014
Delta Wash UV2 D1013

Please contact our technical department for further advice.