



*Stehlin Hostag Ink U.K. Ltd  
Unit D4, Linkmel Close, Longwall Avenue,  
Queens Drive Industrial Estate,  
Nottingham. NG2 1NA  
Tel: 0115 986 0477  
Fax: 0115 986 2681*

Date of Issue: 31/05/02

TDS 8/010

## **SALINOFIX 5005 09**

Hardening agent for demineralised water

When demineralisation or reverse osmosis systems are used in print shops to process the tap water, blending to a residual hardness of 8° to 10° d is necessary before the processed water is used for offset printing.

One way of doing this is to blend it with tap water. However, if the quality of the tap water is subject to severe fluctuations because it is drawn from several catchment areas, or if high concentrations of other detrimental ingredients (such as corrosion-promoting chlorides) are present, this is no longer possible.

In such cases we recommend using 0.5% SALINOFIX in demineralised water.

SALINOFIX is a product used to adjust the total hardness of water for offset printing, and contains no constituents that might interfere with the printing process.

Demineralised water from reverse osmosis systems and water containing SALINOFIX have both a slightly corrosive effect on metals. All pipes and fittings should therefore consist of either plastic or stainless steel.

### **Quantity to be added**

0.5% SALINOFIX added to demineralised water.

### **Packaging**

25kg Plastic Buckets